

# SPECIALTY ACCESSORIES



## SPECIALTY LANCE ACCESSORIES /JOB SPECIFIC

PART #	DESCRIPTION	GPM	PSI	TEMP	INLET	OUTLET	WT
<b>Gutter Cleaner</b>							
<b>D20011</b>	Gutter Cleaner, 12" NOTE: For use w/#5.0 or Larger Nozzle	10.5	3000	195° F	1/4"QCP	1/4"QCS	.55
<b>Water Brooms</b>							
<b>100869</b>	Water Broom, 12" w/3-Nozzles	10.5	3000	195° F	1/4"NPT-F	65deg (3)	2.8
<b>100870</b>	Water Broom, 16" w/4-Nozzles	10.5	3000	195° F	1/4"NPT-F	65deg (4)	4.0
<b>Foamers</b>							
<b>YLS12T</b>	Foamer Kit w/1 Liter Tank	6.5	3200	140° F	1/4"BSP-F	1.5mm	1.1
<b>14.5001</b>	Foamer Kit w/1 Liter Tank *1/4"QC Plug & 22mm Twist Coupler Plug Included	18-53	5000	140° F	1/4"FPT*	1.2mm	1.6
<b>Rotating Brush</b>							
<b>YROTOBRUSH*</b>	Rotating Brush, Natural Bristle *Excellent for Painted Finishes	8	435	140° F	1/4"BSP-M	N/A	1.8
<b>Sand Blasters</b>							
<b>VSANDBLST*</b>	Sandblast Kit, Industrial *Sandblast Nozzle w/Tungsten Carbide Tip +Adjustable Sand Intake +Sand Probe +25' Sand Hose *#3.5 Nozzle Included	10	5075	140° F	1/4"QCP	1.22mm	8.9
<b>V290001</b>	Replacement Carbide Nozzle, Fits VSANDBLST & DWSDBTK						
<b>DWSDBTK*</b>	Sandblast Kit, Industrial *Sandblast Nozzle w/Tungsten Carbide Tip +Adjustable Sand Intake +Sand Probe +25' Sand Hose NOTE: 1/4"MEG Nozzle NOT Included & Proper Nozzle MUST be Installed Prior to Use	3-10.5	5500	200° F	1/4"QCP	1/4"FPT	10.0
<b>ASB001*</b>	DWSDBTK w/915040M Nozzle *#4.0 Nozzle Included, Perfect for 4@4000 Applications	2-5.5	5500	200° F	1/4"QCP	1.32mm	10.0



Shown w/  
Optional Wheel  
& Handle Kit

ASH06

## SAND HOPPER ASSEMBLY



PART #	DESCRIPTION	WT
<b>HTCP</b> ASH06	Sand Hopper Assem. w/Heavy Duty 6500psi Carbide Sand Head	95
<b>HTCP</b> ASH10	Wheel Kit w/Handle Assembly	12

NOTE: Powder coated steel, 300# capacity. Designed to mount on Hydro Tek trailers but can also be mounted to most flat trailers and truckbeds. Includes 50' of 3/4" Crush-Proof PVC sand hose, size 6.0 x 5" nozzle, 3/4" sand couplers to make a complete system.

DON'T SEE THE EXACT ACCESSORY THAT YOU NEED, CALL US TODAY. (504) 888-8989

# SPECIALTY ACCESSORIES

## SUTTNER



999 001 540

### SUTTNER SLUDGE PUMP HOSE -HIGH OUTPUT

PART #	LGTH	FLOW RATE	INLET	ORIFICE	WT
--------	------	-----------	-------	---------	----

999 001 540	15'	11:1	M22-M	#4.0 x 0°	7.5
-------------	-----	------	-------	-----------	-----

NOTE: Attaches to any PressureWasher & turns it into a High Output Pump. Great for Flood Cleanup, Car Wash Pits, Draining Pools, or Chemical Spills. Vacuums up Liquid Slurries at a Ratio of 11:1 (Example: 4 GPM will Produce 44 GPM Output)  
HOSE BARB: 1-1/2" / PSI: 4000 / TEMP: 104° F

### MUCK SCUPPER SLUDGE & SLURRY EVACUATION TOOL



	PART #	LGTH	INLET	ORIFICE	WT
<b>HTCP</b>	ANS04	15'	1/4" QCP	#4.0	10.5
<b>HTCP</b>	ANS55	15'	1/4" QCP	#5.5	10.5
<b>HTCP</b>	DHB17	1-1/2" Discharge Hose, PER FOOT			

NOTE: Turn your pressure washer into a sludge, slurry, water evacuation tool. Pressure energy of spray from pressure washer wand creates suction that pulls water, up to 87gpm, through a 15' heavy wall 1 1/2" discharge hose. Ideal for clean out of sump pots, draining a fountain or pond, and flood cleanup.

Watch it in action at: [www.hydrotek.us/accessories.htm](http://www.hydrotek.us/accessories.htm)



ANS04

Connect to your existing 1/4" pressure washer wand quick connect coupler, no other tools required

### UNDERCARRIAGE WAND



	PART #	PSI	GPM	LENGTH	INLET	OUTLET	WT
<b>HTCP</b>	AVUN1	5000	6	52	1/4" QC	1/4" QC	7.5

For removing dirt and grime from underneath a vehicle, try HydroTek's undercarriage wand with casters. Simply attach the wand to your power washer gun, insert QC nozzle and roll under vehicle. The undercarriage wand is also ideal for cleaning under boat trailers and motor homes.



### UNDERCARRIAGE WASHER



	MODEL	PSI	GPM	COVER	COVER DIAM.	WT
<b>HTCP</b>	ANTUN	5000	6	SS	24"	27

Clean the undercarriage of trucks, boats, and farm equipment. Attach this accessory to a hot or cold pressure washer to effortlessly remove grime from the underside of vehicles and equipment. If you need to clean concrete, simply reverse the casters and flip the deck over to be used as an efficient flat surface cleaner. Rust resistant, stainless steel construction, with an aluminum spray bar, to ensure a long life of use even in corrosive environments.

NOTE: 7" clearance height needed, 210°F Max.



DON'T SEE THE EXACT LANCE THAT YOU NEED, CALL US TODAY.  
(504) 888-8989 or Toll Free 800-992-7448