

HOTSHOT SERIES

GAS, DIRECTDRIVE



POWERED by
HONDA™

GX390 Engine



RRV4G40D-F24 Pump

4012-10A

4GPM@ 4000PSI

Standard Accessories

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- Maxi-Flo20%chemical injector assembly w/quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle

Standard Options

- ATK005 Adjustable Thermostat
- BRK100 Brake Kit
- HRK415 Hose Reel Kit, 150' x 3/8" max. w/ no add'l hose
- MC-B135 Machine Cover Blue Poly Marine Fabric

NOTE:AR, CAT, and VIPER gear drive pumps available – consult factory.

Standard Features

- Rugged powder coated steel roll cage frame w/ lifting hook & 13" flat-free tires & threaded axles
- 4-wheel dimensions: 39" L x 31" W x 49" H
- Super efficient schedule 80 coil w/ one-piece molded insulation combustion chamber
- Stainless steel coil wrap
- 8 gallon poly diesel fuel tank w/ fuel filter
- Commercial/Industrial grade engines
- Reliable Beckett burners
- High limit over temp protection
- Safety pressure relief valve
- Thermo-sensor(prevents over heating in bypass mode)

NOTE:Gasoline Honda and Diesel powered models include electric start, and battery w/ marine battery box.

AUTHORIZED DEALER:

Pressure Zone

2813 Richland Ave. Metairie, LA 70002

(504) 888-8989 | 800-992-7448

www.PressureZone.com

Pressure-Pro®