

HP PRESSURE STEAMERS

HP SERIES: DIESEL HEATED, ELECTRIC MOTOR



EXCEPTIONAL HEAT OUTPUT FOR STUBBORN GRIME

HYDROTEK

PRESSURE STEAMER

HOT/COLD/STEAM-PORTABLE, ELECTRIC POWERED, DIESEL HEATED

HP
SERIES

High Heat / High Flow System:

The balance of heat and flow increases your cleaning power providing a consistent superior performance. Auto ignition for peace of mind & ease of operation. High capacity diesel burner with higher temperature rise for faster cleaning.

SpiraLast™ Coil:

The coil is a Hydro Tek manufactured SpiraLast™ heating coil. Robotically fused 1/2" schedule 80 steel pipe is cold rolled to protect the steel pipe from fatigue and the spiral coil is then surrounded by ceramic insulation and stainless enclosure with double-wall end caps. Ask your dealer about the Lifetime Coil Warranty.

Auto Start and Time Delay Shutdown:

Operator has total control over the system from the trigger gun. This added convenience not only saves time and effort, it reduces wear and overheating of the pump and produces an energy efficient system that outperforms the traditional manual on/off.

Stainless Steel Coil Housing, Frame and Panels:

Rust-proof durable panels offer corrosion resistance and protection of your valuable investment from the harshest environments. Keeps your machine looking like new for years to come. Screw connects provide easy removal for full access to all major components and the Ultimate in serviceability.

Adjustable Temperature with Steam Setting:

Front mounted controls allows quick and easy adjustments of temperature and steam settings with higher heat than comparable washers for your toughest cleaning applications.

NEMA4 - Water Tight Control Panel:

ETL certified to UL1776 Class 2, for use in wash-down area, exceeding Industry standards. Special Hydro Tek control box features easy to use controls and provides instant access to electronics. **Dual voltage switch** on most 230v models allows you to simply flip a switch to change to 208v power supply.

CAT Belt Driven Pump:

Belt drive pump with low RPM drive - cooler, quieter, continuous duty performance. These Industrial triplex pumps outperform the competition in longevity - featuring concentrically bored & polished, graphite impregnated ceramic plungers with advanced seal design.

Diesel Fuel Tank with filtration:

Heavy Duty "roto-molded" rust free fuel tank with water separating fuel filter to protect against contaminated fuel. Extended run time (up to 5 hrs) eliminates interruptions.

Chemical Injection:

Equipped with inlet soap injection combined with precision chemical metering valve and float tank to inject soap at full pressure for optimal cleaning effectiveness. Panel mounted controls enable the operator to vary the mixture of soap or other additives with ease.


Portability:

HP Series comes standard with four large tires mounted on stainless axles and two lift handles.

More Standard Features...

- Heavy duty industrial motor with thermal overload protection
- Burst disc technology for operator safety
- Insulated quick connect nozzles
- 50' of heavy duty high pressure hose
- Stainless adjustable pressure wand and heavy duty trigger gun
- Panel mounted hour meter

Unmatched Durability: The HP is a proven model manufactured and refined for over two decades.



Specifications

Model	PSI	GPM	Temp.	HP	Voltage
HP20005E8	2000	4.3	250° F	6.5	208/230v - 1ph
HP22005E2	2200	4.3	250° F	6.5	230v - 1ph
HP30004E2 *	3000	3.9	250° F	8	208/230v - 1ph
HP35005E3	3500	4.3	250° F	10	208/230v - 3ph
HP35005E4	3500	4.3	250° F	10	460v - 3ph

Specifications may vary, consult factory for custom models

*HP30004E2 is not ETL Listed / UL1776 Certified, requires additional options

Dimensions: 46" x 29" x 39"

Optional Accessories...

Hose and wand extension, Stainless hose reel



HYDRO TEK
CLEANING EQUIPMENT MFG.

Authorized Dealer:
PRESSURE ZONE
2813 Richland Ave. Metairie, LA 70002
(540) 888-8989 | 800-922-7448
www.pressurezone.com